

3/4" AIR IMPACTTOOLS



DWT GmbH
Zur Halbinsel 12
45356 Essen
Tel: 0201-45099-0
Fax: 0201-45099-99
info@dwt-gmbh.de
www.dwt-gmbh.de



2141S 3/4" Composite Impactool ★★ ★



The smallest and the lightest 3/4" Impactool with unmatched reliability.

- **More Power:** Over 1 600 Nm (1 200 ft-lb) of maximum torque in reverse, an extremely compact size and only 3.24 kg (7.15 lb). This is the best power-to-weight and size ratio in its class.
- **More Control:** The only 3/4" Impactool weighting less than 3.3 kg (7.25 lb) will significantly reduce stress on operator and increase productivity. Its extremely compact size will also provide access even to tightest spaces. Patented one-hand forward and reverse switch, contoured feather-touch trigger, wide range of power regulator setting and always maximum power in reverse, provide ultimate control and increased efficiency.
- **Tougher:** The TwinHammer™ Plus impact mechanism provides unmatched durability.



2161XP 3/4" Impactool ★★ ★

- 1 695 Nm (1 250 ft-lb) of maximum torque in reverse.
- TwinHammer™ impact mechanism.
- Heavy-duty steel hammer case and aluminum housing.
- Sensitive trigger and 3-position power regulator in forward.
- Options: Horizontal suspension bail, ordering no. 2161-366 and exhaust hose adapter, ordering no. 2161-123.



2161XP-6 3/4" Impactool with extended anvil ★★ ★

- Same as 2161XP with 150 mm extended anvil.

261-EU 3/4" Impactool ★★

- 1 491 Nm (1 100 ft-lb) of maximum torque in reverse.
- Jumbo Hammer impact mechanism.
- Pressure-feed lubrication system.
- Silenced, through handle exhaust.



261-6-EU 3/4" Impactool with extended anvil ★★

- Same as 261-EU with 150 mm extended anvil.

258 3/4" Impactool ★

- 1 360 Nm (1 100 ft-lb) of maximum torque in reverse.
- Ball & Cam impact mechanism.
- Fully adjustable power in forward and reverse.
- Silenced, through handle exhaust.



Specifications at 6.2 bar (90 psi)

	2141S	2161XP	2161XP-6	261-EU	261-6-EU	258
Ordering number	89939060	01372085	01372093	01343094	01343185	22039432
Square drive	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Bolt capacity	M27	M27	M27	M27	M27	M27
Maximum torque in reverse (ft-lb • Nm)	1200 • 1627	1250 • 1695	1250 • 1695	1100 • 1495	1100 • 1495	1000 • 1360
Working torque (ft-lb)	200-900	300-1000	300-1000	200-900	200-900	200-800
Working torque (Nm)	270-1220	407-1356	407-1356	270-1220	270-1220	270-1088
Maximum free speed (rpm)	6500	6000	6000	5500	5500	6200
Impacts per minute	1 175	1 025	1 025	1 000	1 000	1 100
Tool weight (kg)	3.24	5.35	5.90	5.60	6.20	4.90
Overall length (mm)	211	216	368	224	376	249
Air inlet diameter (in/NPTF)	3/8	3/8	3/8	3/8	3/8	3/8
Minimum hose size diameter (mm)	13	13	13	13	13	13
Average air consumption (cfm • l/min)	9.5 • 269	10 • 280	10 • 280	9.5 • 269	9.5 • 269	8 • 226
Air consumption at load (cfm • l/min)	40 • 1133	46 • 1288	46 • 1288	38 • 1076	38 • 1076	30 • 835
Impacting sound pressure (dBA)	96.6	94.7	94.7	98.1	98.1	96.6
Vibration level (m/s ²)	5.9	6.5	8.1	6.1	6.8	3.4