

Expert EXT Series

(E) ingersoll Panni

24.18.

UR Ingersoil Rand

900

05

e.

Calibration Equipment





Competition is driving product quality requirements to new levels. Meeting these demands requires keeping your processes in control and your tools working within specifications.

The solution: **Expert EXT Series calibration equipment**

Our Expert EXT Series calibration equipment is the ideal quality-control companion for assembly operations with stringent torque control standards. Choose from our offering of easy-to-use torque testers, analyzers, transducers, and joint kits to set up and calibrate your full portfolio of precision tools.

EXTT Series torque testers

The EXTT Series torque testers comprises four models of torque testers with integrated transducers that allow rapid and accurate torque checking of lower torque fastening tools from 0.1 to 30 Nm (1 to 265 in-lb). The EXTT's enhanced features include track and peak modes for most hand and power tools, a pulse mode that measures and counts pulses of pulse tools, and a click mode for hand-click wrenches.

EXTA Series torque analyzer

The EXTA Series torque analyzer shares the same compact, sleek design but is designed for portability and use with a broad range of external transducers: whether torque only or torque and angle. It can dynamically measure and record the output of precision fastening tools on the application or the workbench in both directions when coupled with our automatically recognized Smart or Industry Standard transducers. Joint simulators are also available to emulate different joint rates from hard to soft and can be used with both stationary and rotary transducers when working away from the application.

Expert EXT Series — torque testers and analyzers

The second second

Power and hand tool compatibilitymeans only one system is needed to setup and calibrate all of your precision tools.

Durable, ESD-safe construction holds up to factory environments.

Full statistical capabilities include Cp, Cpk, Pp, Ppk, CMK, CAM, range, mean, and standard deviation.

Compact and lightweight with rechargeable battery provides ease of use and portability on the assembly line and space savings on the workbench.



Large LCD screen shows clear, easy-to-read test results and menus.

EXTT-30 shown with

integrated transducer

and rundown adapter.

- Solution Monitors torque, angle, time, and pulse count
- Reads in peak, click, pulse, or track mode
- Stores 200 time-stamped readings
- Auto-recognition of Smart transducers
- Seven units of measure
- Selectable filter frequencies
- DC tool calibration via ICS software
- Selectable power-save settings
- Selectable languages include English, French, German, Italian, and Spanish

ingersollrandproducts.com/tools

EXTA SERIES — EXPERT TORQUE ANALYZER						
Model	External Transducer	Data Transfer	Auto Recognition	LCD Screen		
EXTA	Smart (UTA) or Industry Standard (IS)	PC or Printer	Yes	62 x 62 mm		

EXTT SERIES — EXPERT TORQUE TESTERS							
Model	in-lb	Nm	Rundown Adapter*	Ru			
EXTT-1	0.88 - 8.8	0.1 – 1	ETT-RA-1	H			
EXTT-4	3.50 – 35	0.4 - 4	ETT-RA-4	H			
EXTT-12	10.6 – 106	1.2 – 12	ETT-RA-12	E			
EXTT-30	26.5 – 265	3.0 – 30	ETT-RA-30	E			

* EXTT tester includes rundown adapter, carrying case, battery charger, manuals, and a certicficate of calibration. EXTA analyzer includes carrying case, battery charger, manuals, and neck strap.

Soft-touch keypad makes menu navigation and test setup simple.

Audible and visible indicators give High, Low, and Pass cycle status.

Quick download of results to printer or PC for data analysis, graphing, and documentation or calibration

of DC electric tools using ICS software.



209 x 194 x 78 mm Weight 2.2 lb / 1.0 kg (EXTA) 4.5 lb / 2.1 kg (EXTT)

Dimensions

Literature



Audit wrench Assembly tools IRPS-1007-052 ASM-1106-128

QA4/6/8 tools Fixtured systems DC tools IRITS-0109-008 IRPS-1007-053





Rotary transducers

Stationary transducer with joint simulator

Accessories

Transducer	rs		1	n 1		
Industry Smart Transducers						
Standard	Torque only	Torque and Angle	(in-lb) ft-lb	Nm	in	
ROTARY				_		
TR2H4	-	-	(1.0 - 18)	0.10 - 2	1/4 O	
TR5H4	TRD5H4	TRDA5H4	(2.2 - 44)	0.25 - 5	1/4 O	
TR20H4	TRD20H4	TRDA20H4	(9.0 - 180)	1 - 20	1/4 O	
TR20S4	TRD20S4	TRDA20S4	(9.0 - 180)	1 - 20	1/4 🗅	
TR75S6	TRD75S6	TRDA75S6	2.8 - 55	3.8 - 75	3/8 🗅	
TR180S8	TRD180S8	TRDA180S8	6.7 - 133	9 - 180	1/2 🗗	
TR250S12	-	-	9.2 - 185	12.5 - 250	3/4 🗅	
TR500S12	TRD500S12	TRDA500S12	18.5 - 370	25 - 500	3/4 🗅	
STATIONARY						
TS30S4	TSD28S4	-	1.1 - 22	1.5 - 30	1/4	
TS150S6	TSD135S6	-	5.5 - 110	7.5 - 150	3/8	
TS300S8	TSD270S8	-	11 - 221	15 - 300	1/2	
TS1000S12	TSD1000S12	-	37 - 738	50 - 1000	3/4	
1.1.1.1.0.0.1	1.1					

Model	Includes Transducer	Joint Simulator Bolt Service Kit	ft-lb	Nm	in		
ROTARY							
JKR20	No	JKS30-BKIT	0.75 - 15	1.0 - 20	1/4		
JKR75	No	JKS150-BKIT	2.8 - 55	3.8 - 75	3/8		
JKR180	No	JKS300-BKIT	6.7 - 133	9.0 - 180	1/2		
JKR500	No	JKS1000-BKIT	18.5 - 370	25.0 - 500	3/4		
STATIONAR	Y						
JKS30	No	JKS30-BKIT	0.75 - 15	1.0 - 20	1/4		
JKS150	No	JKS150-BKIT	2.8 - 55	3.8 - 75	3/8		
JKS300	No	JKS300-BKIT	6.7 - 133	9.0 - 180	1/2		
JKS1000	No	JKS1000-BKIT	18.5 - 370	25.0 - 500	3/4		
JKST30	TS30S4	JKS30-BKIT	1.1 - 15	1.5 - 20	1/4		
JKST150	TS150S6	JKS150-BKIT	5.5 - 55	7.5 - 75	3/8		
JKST300	TS300S8	JKS300-BKIT	11.0 - 133	15.0 - 180	1/2		
JKST1000	TS1000S12	JKS1000-BKIT	37.0 - 37-	50.0 - 500	3/4		

Manuals

Series	User Manual	Quick Start Guide	Safety	
EXT Series	45652906	45655859	45654696	

To find manuals on the Web: www.irtechpubs.com

To order Ingersoll Rand literature please e-mail inlitorders@kencook.com



IRITS-1107-043

Pulse tools SW041107



Torque arms IRPS-0907-044



Cordless tools VSS-0806-060



Feed drill 52475-AT-C



Qi impacts IRITS-1008-118



Ingersoll Rand fastening portfolio

crib, calibration lab, or workstation.

Ingersoll Rand offers a full line of production fastening equipment, including air and electric screwdrivers, nutrunners, drills, riveters, pulse tools, as well as hand-held and multispindle fixtured DC nutrunners. Whether you need a solution for a single, specific application or an entire assembly line, you can trust our century of tool design experience to meet your needs.





Ideal for use with a broad range of external transducers to test output of assembly tools on the application or wherever torque verification is required.

Take advantage of our extensive line of accessories and services to optimize your assembly and quality assurance processes.

Transducers		Joint Simulator Kits		Torque Wrench	Other Accessories		
Rotary	Stationary	Rotary	Stationary	Rundown Adaptor	Cordless		ETA 2 TC
				(Cable - IS transducer Cable - PC Cable - printer Neck strap Port saver - 9 pin Port saver - 25 pin Battery charger	ETA2-TC ETA2-PC99 ETA2-P925 ETA2-STRAP EXT-PS9 ETA2-P525 EXT-BC

DWT GmbH | Wilhelm-Tenhagen-Str. 5 | 46240 Bottrop | Tel. +49(0) 2041 77144-0 Fax. +49(0) 2041 77144-99 | info@dwt-gmbh.de | www.dwt-gmbh.de