






# Druckluft-Schläuche



## Spiralschläuche

- Temperaturbereich: -40 bis +38 °C.
- Maximaler Betriebsdruck: 8 bar bei 24 °C.

	CPN	 mm	 NPT	 m	 m	 m
<b>Gelb</b>						
<b>34102</b>	92833375	6	1/4"	3	2,5	0,15
<b>34202</b>	92833383	6	1/4"	6	5	0,31
<b>34302</b>	92833391	6	1/4"	9	8	0,43
<b>35102</b>	92833409	8	1/4"	3	2,5	0,14
<b>35202</b>	92832526	8	1/4"	6	5	0,30
<b>35302</b>	92833417	8	1/4"	9	8	0,46
<b>IR36103</b>	92835172	9,5	1/4"	3	2,5	0,15
<b>IR36203</b>	92835180	9,5	1/4"	6	5	0,34
<b>IR36303</b>	92835198	9,5	1/4"	9	8	0,52
<b>IR36102</b>	92835149	9,5	3/8"	3	2,5	0,15
<b>IR36202</b>	92835156	9,5	3/8"	6	5	0,34
<b>IR36302</b>	92835164	9,5	3/8"	9	8	0,52
<b>IR37102</b>	92835206	13	1/2"	3	2,5	0,16
<b>IR37202</b>	92835214	13	1/2"	6	5	0,38
<b>Blau</b>						
<b>IR36713</b>	88098991	9,5	3/8"	6	5	0,34
<b>IR36715</b>	88099015	9,5	3/8"	9	7,5	0,52

